

Package ‘moranajp’

August 5, 2026

Title Morphological Analysis for Japanese

Version 0.9.8

Description Supports morphological analysis for Japanese by using
'MeCab' <<https://taku910.github.io/mecab/>>,
'Sudachi' <<https://github.com/WorksApplications/Sudachi>>,
'Chamame' <<https://chamame.ninjal.ac.jp/>>,
or 'Ginza' <<https://github.com/megagonlabs/ginza>>.
Can input a data.frame and obtain all results of 'MeCab' and the row
number of the original data.frame as a text id.

License MIT + file LICENSE

Depends R (>= 4.2.0)

URL <https://github.com/matutosi/moranajp>,
<https://matutosi.github.io/moranajp/>

BugReports <https://github.com/matutosi/moranajp/issues>

Imports dplyr, ggplot2, ggraph, grid, igraph, purrr, rlang, rvest,
stats, stringr, stringi, tibble, tidyr, utils

Suggests devtools, knitr, rmarkdown, spelling, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Language en-US

NeedsCompilation no

Author Toshikazu Matsumura [aut, cre]

Maintainer Toshikazu Matsumura <matutosi@gmail.com>

Repository CRAN

Date/Publication 2026-08-05 08:20:06 UTC

Contents

add_group	2
add_id	3
add_sentence_no	4
add_text_id	4
clean_up	5
combine_words	6
draw_bigram_network	7
escape_japanese	9
iconv_x	9
make_groups	10
moranajp_all	12
neko	14
neko_chamame	15
neko_ginza	16
neko_mecab	17
neko_sudachi_a	18
out_cols_chamame	19
remove_brk	21
review	22
review_chamame	22
review_ginza	23
review_mecab	24
review_sudachi_a	25
stop_words	26
synonym	26
unescape_utf	27
Index	28

add_group	<i>Add group id column into result of morphological analysis</i>
-----------	--

Description

Add group id column into result of morphological analysis

Usage

```
add_group(
  tbl,
  col,
  brk = "EOS",
  grp = "group",
  cond = NULL,
  end_with_brk = TRUE
)
```

Arguments

tbl	A dataframe
col	A string to specify the column including breaks
brk	A string to specify breaks
grp	A string to specify group
cond	A string to specify condition
end_with_brk	A logical

Value

A dataframe

Examples

```
brk <- "EOS"
tbl <- tibble::tibble(col_a = c(rep("a", 2), brk, rep("b", 3), brk, rep("c", 4), brk))
add_group(tbl, col = "col_a", grp = "text_id")
add_group(tbl, col = "col_a", end_with_brk = FALSE)
```

add_id	<i>Add id in each group</i>
--------	-----------------------------

Description

Add id in each group

Usage

```
add_id(tbl, grp = "group", id = "id")
```

Arguments

tbl	A dataframe
grp, id	A string to specify the column of group and id

Value

A dataframe

Examples

```
brk <- "EOS"
tbl <- tibble::tibble(col=c(rep("a", 2), brk, rep("b", 3), brk, rep("c", 4), brk))
add_group(tbl, col = "col") |>
  add_id(id = "id_in_group")
```

add_sentence_no	<i>Wrapper function for add_group() to add sentence id</i>
-----------------	--

Description

Wrapper function for add_group() to add sentence id

Usage

```
add_sentence_no(df)
```

Arguments

df	A dataframe
----	-------------

Value

A dataframe

Examples

```
review_mecab |>
  unescape_utf() |>
  add_sentence_no() |>
  print(n=200)
```

add_text_id	<i>Add id column into result of morphological analysis</i>
-------------	--

Description

Internal function for moranajp_all(). Add text_id column when there is brk ("BP"). "BP": Break Point of moranajp

Usage

```
add_text_id(tbl, method, brk = "BP")
```

Arguments

tbl	A tibble or data.frame.
method	A text. Method to use: "mecab", "ginza", "sudachi_a", "sudachi_b", "sudachi_c", or "chamame". "a", "b" and "c" specify the mode of splitting. "a" split shortest, "b" middle and "c" longest. See https://github.com/WorksApplications/Sudachi for detail. "chamame" use https://chamame.ninjal.ac.jp/ and rvest.
brk	A string of break point

Value

A data.frame with column "text_id".

clean_up	<i>Clean up result of morphological analyzed data frame</i>
----------	---

Description

Clean up result of morphological analyzed data frame

Usage

```
clean_up(df, add_depend = FALSE, ...)

pos_filter(df)

add_depend_ginza(df)

delete_stop_words(df, use_common_data = TRUE, add_stop_words = NULL, ...)

replace_words(
  df,
  synonym_df = tibble::tibble(),
  synonym_from = "",
  synonym_to = "",
  ...
)

term_lemma(df)

term_pos_0(df)

term_pos_1(df)
```

Arguments

df	A dataframe including result of morphological analysis.
add_depend	A logical. Available for ginza
...	Extra arguments to internal functions.
use_common_data	A logical. TRUE: use data(stop_words).
add_stop_words	A string vector adding into stop words. When use_common_data is TRUE and add_stop_words are given, both of them will be used as stop_words.
synonym_df	A data.frame including synonym word pairs. The first column: replace from, the second: replace to.

synonym_from, synonym_to

A string vector. Length of synonym_from and synonym_to should be the same. When synonym_df and synonym pairs (synonym_from and synonym_to) are given, both of them will be used as synonym.

Value

A data.frame.

Examples

```
data(neko_mecab)
data(neko_ginza)
data(review_sudachi_c)
data(synonym)
synonym <-
  synonym |> unescape_utf()

neko_mecab <-
  neko_mecab |>
  unescape_utf() |>
  print()

neko_mecab |>
  clean_up(use_common_data = TRUE, synonym_df = synonym)

review_ginza |>
  unescape_utf() |>
  add_sentence_no() |>
  clean_up(add_depend = TRUE, use_common_data = TRUE, synonym_df = synonym)

review_sudachi_c |>
  unescape_utf() |>
  add_sentence_no() |>
  clean_up(use_common_data = TRUE, synonym_df = synonym)
```

combine_words

Combine words after morphological analysis

Description

Combine words after morphological analysis

Usage

```
combine_words(df, combi, sep = "-")
```

```
combi_words(x, combi, sep = "-")
```

Arguments

df	A dataframe including result of morphological analysis.
combi	A string (combi_words()) or string vector (combine_words()) to combine words.
sep	A string of separator of words
x	A pair of string joining with "-"

Value

A data.frame with combined words.

Examples

```
x <- letters[1:10]
combi <- c("b-c")
combi_words(x, combi)
expected <- c("a", "bc", NA, "d", "e", "f", "g", "h", "i", "j")
testthat::expect_equal(combi_words(x, combi), expected)

df <- unescape_utf(review_chamame) |> head(20)
combi <- unescape_utf(
  c("\u751f\u7269-\u591a\u69d8", "\u8fb2\u5730-\u306f",
    "\u8fb2\u7523-\u7269", "\u751f\u7523-\u3059\u308b"))
combine_words(df, combi)
```

draw_bigram_network	<i>Draw bigram network using morphological analysis data.</i>
---------------------	---

Description

Draw bigram network using morphological analysis data.

Usage

```
draw_bigram_network(df, draw = TRUE, ...)

bigram(df, group = "sentence", depend = FALSE, term_depend = NULL, ...)

trigram(df, group = "sentence")

bigram_depend(df, group = "sentence")

bigram_network(bigram, rand_seed = 12, threshold = 100, ...)

word_freq(df, big_net, ...)

bigram_network_plot(
```

```

big_net,
freq,
...,
arrow_size = 5,
circle_size = 5,
text_size = 5,
font_family = "",
arrow_col = "darkgreen",
circle_col = "skyblue",
x_limits = NULL,
y_limits = NULL,
no_scale = FALSE
)

```

Arguments

df	A dataframe including result of morphological analysis.
draw	A logical.
...	Extra arguments to internal functions.
group	A string to specify sentence.
depend	A logical.
term_depend	A string of dependent terms column to use bigram.
bigram	A result of bigram().
rand_seed	A numeric.
threshold	A numeric used as threshold for frequency of bigram.
big_net	A result of bigram_network().
freq	A numeric of word frequency in bigram_network. Can be got using word_freq().
arrow_size, circle_size, text_size	A numeric.
font_family	A string.
arrow_col, circle_col	A string to specify arrow and circle color in bigram network.
x_limits, y_limits	A Pair of numeric to specify range.
no_scale	A logical. FALSE: Not draw x and y axis.

Value

A list including df (input), bigram, freq (frequency) and gg (ggplot2 object of bigram network plot).

Examples

```

sentences <- 50
len <- 30
n <- sentences * len

```



```
x <- letters
prob <- (length(x):1) ^ 3
df <-
  tibble::tibble(
    lemma = sample(x = x, size = n, replace = TRUE, prob = prob),
    sentence = rep(seq(sentences), each = len))
draw_bigram_network(df)
```

escape_japanese	<i>Generate code like "stringi::stri_unescape_unicode(...)"</i>
-----------------	---

Description

Generate code like "stringi::stri_unescape_unicode(...)"

Usage

```
escape_japanese(x)
```

Arguments

x A string or vector of Japanese

Value

A string or vector

Examples

```
stringi::stri_unescape_unicode("\\u8868\\u5c64\\u5f62") |>
  print() |>
  escape_japanese()
```

iconv_x	<i>iconv x</i>
---------	----------------

Description

iconv x

Usage

```
iconv_x(x, iconv = "", reverse = FALSE)
```

Arguments

x	A string vector or a tibble.
iconv	A text. Convert encoding of MeCab output. Default (""): don't convert. "CP932_UTF-8": iconv(output, from = "Shift-JIS" to = "UTF-8") "EUC_UTF-8" : iconv(output, from = "eucjp", to = "UTF-8") iconv is also used to convert input text before running MeCab. "CP932_UTF-8": iconv(input, from = "UTF-8", to = "Shift-JIS")
reverse	A logical.

Value

A string vector.

make_groups	<i>Make groups by splitting string length</i>
-------------	---

Description

Using 'MeCab' for morphological analysis. Keep other colnames in dataframe.

Usage

```
make_groups(
  tbl,
  text_col = "text",
  length = 8000,
  tmp_group = "tmp_group",
  str_length = "str_length"
)

make_groups_sub(tbl, text_col, n_group, tmp_group, str_length)

max_sum_str_length(tbl, tmp_group, str_length)
```

Arguments

tbl	A tibble or data.frame.
text_col	A text. Colnames for morphological analysis.
length	A numeric.
tmp_group, str_length	A string to use temporary.
n_group	A numeric.

Value

A tibble. Output of morphological analysis and added column "text_id". NULL when method = "chamame" and web chamame is not available.

A string

A string

A string

A character vector

A character vector

A character vector

A character vector

A character vector

A data.frame

Examples

```
# sample data of Japanese sentences
data(neko)
neko <-
  neko |>
  unescape_utf()

## Not run:
# chamame: need to connect https://chamame.ninjal.ac.jp/ .
neko |>
  moranajp_all(method = "chamame") |>
  print(n=100)

## End(Not run)
## Not run:
# Need to install 'mecab', 'ginza', or 'sudachi' in local PC

# mecab
bin_dir <- "d:/pf/mecab/bin"
iconv <- "CP932_UTF-8"
neko |>
  moranajp_all(text_col = "text", bin_dir = bin_dir, iconv = iconv) |>
  print(n=100)

# ginza
neko |>
  moranajp_all(text_col = "text", method = "ginza") |>
  print(n=100)

# sudachi
bin_dir <- "d:/pf/sudachi"
iconv <- "CP932_UTF-8"
neko |>
  moranajp_all(text_col = "text", bin_dir = bin_dir,
```

```

        method = "sudachi_a", iconv = iconv) |>
    print(n=100)

## End(Not run)

```

moranajp_all

Morphological analysis for a specific column in dataframe

Description

Using 'MeCab' for morphological analysis. Keep other colnames in dataframe.

Usage

```

moranajp_all(
  tbl,
  bin_dir = "",
  method = "mecab",
  text_col = "text",
  option = "",
  iconv = "",
  col_lang = "jp",
  dic = "unidic-spoken"
)

moranajp(tbl, bin_dir, method, text_col, option = "", iconv = "", col_lang)

remove_linebreaks(tbl, text_col)

separate_cols_ginza(tbl, col_lang)

make_input(tbl, text_col, iconv, brk = "BP")

make_cmd(method, bin_dir, option = "")

make_cmd_mecab(option = "")

out_cols_mecab(col_lang = "jp")

out_cols_ginza(col_lang = "jp")

out_cols_sudachi(col_lang = "jp")

out_cols_jp()

out_cols_en()

```

```

out_cols()

mecab_all(tbl, text_col = "text", bin_dir = "")

mecab(tbl, bin_dir)

```

Arguments

tbl	A tibble or data.frame.
bin_dir	A text. Directory of mecab.
method	A text. Method to use: "mecab", "ginza", "sudachi_a", "sudachi_b", "sudachi_c", or "chamame". "a", "b" and "c" specify the mode of splitting. "a" split shortest, "b" middle and "c" longest. See https://github.com/WorksApplications/Sudachi for detail. "chamame" use https://chamame.ninjal.ac.jp/ and rvest.
text_col	A text. Colnames for morphological analysis.
option	A text. Options for mecab. "-b" option is already set by moranaip. To see option, use "mecab -h" in command (win) or terminal (Mac).
iconv	A text. Convert encoding of MeCab output. Default (""): don't convert. "CP932_UTF-8": iconv(output, from = "Shift-JIS" to = "UTF-8") "EUC_UTF-8": iconv(output, from = "eucjp", to = "UTF-8") iconv is also used to convert input text before running MeCab. "CP932_UTF-8": iconv(input, from = "UTF-8", to = "Shift-JIS")
col_lang	A text. "jp" or "en"
dic	A text. Dictionary of web chamame. Only used when method = "chamame". See web_chamame() .
brk	A string of break point

Value

A tibble. Output of morphological analysis and added column "text_id". NULL when method = "chamame" and web chamame is not available.

A string

A string

A string

A character vector

A character vector

A character vector

A character vector

A character vector

A data.frame

Examples

```
# sample data of Japanese sentences
data(neko)
neko <-
  neko |>
  unescape_utf()

## Not run:
# chamame: need to connect https://chamame.ninjal.ac.jp/ .
neko |>
  moranajp_all(method = "chamame") |>
  print(n=100)

## End(Not run)
## Not run:
# Need to install 'mecab', 'ginza', or 'sudachi' in local PC

# mecab
bin_dir <- "d:/pf/mecab/bin"
iconv <- "CP932_UTF-8"
neko |>
  moranajp_all(text_col = "text", bin_dir = bin_dir, iconv = iconv) |>
  print(n=100)

# ginza
neko |>
  moranajp_all(text_col = "text", method = "ginza") |>
  print(n=100)

# sudachi
bin_dir <- "d:/pf/sudachi"
iconv <- "CP932_UTF-8"
neko |>
  moranajp_all(text_col = "text", bin_dir = bin_dir,
    method = "sudachi_a", iconv = iconv) |>
  print(n=100)

## End(Not run)
```

neko

The first part of 'I Am a Cat' by Soseki Natsume

Description

The first part of 'I Am a Cat' by Soseki Natsume

Usage

```
neko
```

Format

A data frame with 9 rows and 1 variable:

text Body text. Escaped by `stringi::stri_escape_unicode()`.

Examples

```
data(neko)
neko |>
  unescape_utf()
```

neko_chamame

Analyzed data of neko by chamame

Description

chamame: <https://chamame.ninjal.ac.jp/index.html>

Usage

```
neko_chamame
```

Format

A data frame with 2959 rows and 7 variable: (column names are escaped by `stringi::stri_escape_unicode()`, `stringi::stri_unescape_unicode()` or `unescape_utf()` will show Japanese)

text_id id

\u8868\u5c64\u5f62 result of chamame

\u54c1\u8a5e result of chamame

\u54c1\u8a5e\u7d30\u5206\u985e1 result of chamame

\u54c1\u8a5e\u7d30\u5206\u985e2 result of chamame

\u54c1\u8a5e\u7d30\u5206\u985e3 result of chamame

\u539f\u5f62 result of chamame

Examples

```
data(neko_chamame)
neko_chamame |>
  unescape_utf()
```

neko_ginza

Analyzed data of neko by GiNZA

Description

GiNZA: <https://megagonlabs.github.io/ginza/>

Usage

```
neko_ginza
```

Format

A data frame with 2945 rows and 13 variable:

text_id id

id result of GiNZA

\u8868\u5c64\u5f62 result of GiNZA

\u539f\u5f62 result of GiNZA

UD\u54c1\u8a5e\u30bf\u30b0 result of GiNZA

\u54c1\u8a5e result of GiNZA

\u54c1\u8a5e\u7d30\u5206\u985e1 result of GiNZA

\u54c1\u8a5e\u7d30\u5206\u985e2 result of GiNZA

\u5c5e\u6027 result of GiNZA

\u4fc2\u53d7\u5143 result of GiNZA

\u4fc2\u53d7\u30bf\u30b0 result of GiNZA

\u4fc2\u53d7\u30da\u30a2 result of GiNZA

\u305d\u306e\u4ed6 result of GiNZA

Examples

```
data(neko_ginza)
neko_ginza |>
  unescape_utf()
```

neko_mecab	<i>Analyzed data of neko by MeCab</i>
------------	---------------------------------------

Description

MeCab: <https://taku910.github.io/mecab/>

Usage

```
neko_mecab
```

Format

A data frame with 2884 rows and 11 variable: (column names are escaped by `stringi::stri_escape_unicode()`, `stringi::stri_unescape_unicode()` or `unescape_utf()` will show Japanese)

text_id id

\u8868\u5c64\u5f62 result of MeCab

\u54c1\u8a5e result of MeCab

\u54c1\u8a5e\u7d30\u5206\u985e1 result of MeCab

\u54c1\u8a5e\u7d30\u5206\u985e2 result of MeCab

\u54c1\u8a5e\u7d30\u5206\u985e3 result of MeCab

\u6d3b\u7528\u578b result of MeCab

\u6d3b\u7528\u5f62 result of MeCab

\u539f\u5f62 result of MeCab

\u8aad\u307f result of MeCab

\u767a\u97f3 result of MeCab

Examples

```
data(neko_mecab)
neko_mecab |>
  unescape_utf()
```

neko_sudachi_a	<i>Analyzed data of neko by Sudachi</i>
----------------	---

Description

Sudachi: <https://github.com/WorksApplications/Sudachi>

Usage

neko_sudachi_a

neko_sudachi_b

neko_sudachi_c

Format

A data frame with 3130 rows and 9 variable:

text_id id

\u8868\u5c64\u5f62 result of Sudachi

\u54c1\u8a5e result of Sudachi

\u54c1\u8a5e\u7d30\u5206\u985e1 result of Sudachi

\u54c1\u8a5e\u7d30\u5206\u985e2 result of Sudachi

\u54c1\u8a5e\u7d30\u5206\u985e3 result of Sudachi

\u54c1\u8a5e\u7d30\u5206\u985e4 result of Sudachi

\u54c1\u8a5e\u7d30\u5206\u985e5 result of Sudachi

\u539f\u5f62 result of Sudachi

A data frame with 3088 rows and 9 variable:

A data frame with 3080 rows and 9 variable:

Examples

```
data(neko_sudachi_a)
neko_sudachi_a |>
  unescape_utf()
```

Description

Using <https://chamame.ninjal.ac.jp/> and `rvest`. Because it uses an internet resource, it fails gracefully: when the web service is not available or its response has changed, shows a message and returns `NULL` instead of an error.

Submits a text to web chamame and parses the response. Errors are handled by `web_chamame()`.

Selects the fields by name, NOT by index: web chamame sometimes adds fields, which shifts all the indices. Errors are handled by `web_chamame()`.

The names of the output items of web chamame, in the same order as `out_cols_chamame()`. Only a few items are requested, so the header row of the result corresponds to the cells and the columns can be selected by their names.

Web chamame returns a table even when the analysis failed, e.g. a table with an error page of the server. The positions of the columns are also checked, because they change when web chamame changes its output items. Errors are handled by `web_chamame()`.

Helper function to fail gracefully when an internet resource is not available, as required by the CRAN repository policy.

Usage

```
out_cols_chamame(col_lang = "jp")

web_chamame(
  text,
  col_lang = "jp",
  dic = "unidic-spoken",
  url = "https://chamame.ninjal.ac.jp/index.html"
)

submit_chamame(html, text, col_lang = "jp", dic = "unidic-spoken")

select_chamame_fields(form, dic = "unidic-spoken")

chamame_field(field, item)

cols_chamame()

extract_chamame_cols(tbl, col_lang = "jp")

check_chamame_table(tbl)

read_html_safely(url)
```

```
msg_not_available(url, cnd)
```

```
html_radio_set(form, ...)
```

```
is_radio(fields)
```

Arguments

col_lang	A text. "jp" or "en"
text	A text.
dic	A text. Dictionary of web chamame, e.g. "unidic-spoken", "gendai" or "ipadic". Use the value of the dictionary checkbox in the form.
url	A text. URL to read.
html	A xml_document of web chamame.
form	vest_form object
field	A field in a rvest_form object.
item	A string to specify the item of field.
tbl	A dataframe parsed from the response of web chamame.
cnd	A try-error object.
...	dynamic-dots Name-value pairs giving radio button to modify.
fields	\$fields in vest_form object

Value

A character vector

A dataframe, or NULL when web chamame is not available.

A dataframe

A rvest_form object

A string

A character vector

A dataframe

A dataframe

A xml_document, or NULL when the resource is not available.

A string

vest_form object

A boolean or vector

Examples

```
## Not run:
# Need to connect https://chamame.ninjal.ac.jp/ .
text <-
  paste0("\u3059",
    paste0(rep("\u3082",8),collapse=""),
    "\u306e\u3046\u3061") |>
  unescape_utf()
web_chamame(text)

## End(Not run)
```

remove_brk	<i>Remove break point and other unused rows from the result of morphological analysis</i>
------------	---

Description

Internal function for moranajp_all().

Usage

```
remove_brk(tbl, method, brk = "BP")
```

Arguments

tbl	A tibble or data.frame.
method	A text. Method to use: "mecab", "ginza", "sudachi_a", "sudachi_b", "sudachi_c", or "chamame". "a", "b" and "c" specify the mode of splitting. "a" split shortest, "b" middle and "c" longest. See https://github.com/WorksApplications/Sudachi for detail. "chamame" use https://chamame.ninjal.ac.jp/ and rvest.
brk	A string of break point

Value

A data.frame.

 review

Full text of review article

Description

Full text of review article

Usage

```
review
```

Format

A data frame with 457 rows and 4 variables:

text Body text. Escaped by `stringi::stri_escape_unicode()`. Body text. Escaped by `stringi::stri_escape_unicode()`. Citation is as below. Matsumura et al. 2014. Conditions and conservation for biodiversity of the semi-natural grassland vegetation on rice paddy levees. Vegetation Science, 31, 193-218. doi = 10.15031/vegsci.31.193 https://www.jstage.jst.go.jp/article/vegsci/31/2/31_193/_article/-char/en

chap chapter

sect section

para paragraph

Examples

```
data(review)
review |>
  unescape_utf()
```

 review_chamame

Analyzed data of review by chamame

Description

chamame: <https://chamame.ninjal.ac.jp/index.html>

Usage

```
review_chamame
```

Format

A data frame with 21125 rows and 10 variable (column names are escaped by `stringi::stri_escape_unicode()`, `stringi::stri_unescape_unicode()` or `unescape_utf()` will show Japanese)

```

text_id id
chap chapter
sect section
para paragraph
\u8868\u5c64\u5f62 result of chamame
\u54c1\u8a5e result of chamame
\u54c1\u8a5e\u7d30\u5206\u985e1 result of chamame
\u54c1\u8a5e\u7d30\u5206\u985e2 result of chamame
\u54c1\u8a5e\u7d30\u5206\u985e3 result of chamame
\u539f\u5f62 result of chamame

```

Examples

```

data(review_chamame)
review_chamame |>
  unescape_utf()

```

review_ginza

Analyzed data of review by GiNZA

Description

GiNZA: <https://megagonlabs.github.io/ginza/>

Usage

```
review_ginza
```

Format

A data frame with 19514 rows and 16 variable:

```

text_id id
chap chapter
sect section
para paragraph
id result of GiNZA
\u8868\u5c64\u5f62 result of GiNZA
\u539f\u5f62 result of GiNZA

```

UD\u54c1\u8a5e\u30bf\u30b0 result of GiNZA
 \u54c1\u8a5e result of GiNZA
 \u54c1\u8a5e\u7d30\u5206\u985e1 result of GiNZA
 \u54c1\u8a5e\u7d30\u5206\u985e2 result of GiNZA
 \u5c5e\u6027 result of GiNZA
 \u4fc2\u53d7\u5143 result of GiNZA
 \u4fc2\u53d7\u30bf\u30b0 result of GiNZA
 \u4fc2\u53d7\u30da\u30a2 result of GiNZA
 \u305d\u306e\u4ed6 result of GiNZA

Examples

```
data(review_ginza)
review_ginza |>
  unescape_utf()
```

review_mecab

Analyzed data of review by MeCab

Description

MeCab: <https://taku910.github.io/mecab/>

Usage

```
review_mecab
```

Format

A data frame with 199985 rows and 14 variable: (column names are escaped by `stringi::stri_escape_unicode()`, `stringi::stri_unescape_unicode()` or `unescape_utf()` will show Japanese)

text_id id
chap chapter
sect section
para paragraph
 \u8868\u5c64\u5f62 result of MeCab
 \u54c1\u8a5e result of MeCab
 \u54c1\u8a5e\u7d30\u5206\u985e1 result of MeCab
 \u54c1\u8a5e\u7d30\u5206\u985e2 result of MeCab
 \u54c1\u8a5e\u7d30\u5206\u985e3 result of MeCab
 \u6d3b\u7528\u578b result of MeCab
 \u6d3b\u7528\u5f62 result of MeCab
 \u539f\u5f62 result of MeCab
 \u8aad\u307f result of MeCab
 \u767a\u97f3 result of MeCab

Examples

```
data(review_mecab)
review_mecab |>
  unescape_utf()
```

review_sudachi_a

Analyzed data of review by Sudachi

Description

Sudachi: <https://github.com/WorksApplications/Sudachi>

Usage

```
review_sudachi_a
review_sudachi_b
review_sudachi_c
```

Format

A data frame with 20100 rows and 12 variable:

```
text_id id
chap chapter
sect section
para paragraph
\u8868\u5c64\u5f62 result of Sudachi
\u54c1\u8a5e result of Sudachi
\u54c1\u8a5e\u7d30\u5206\u985e1 result of Sudachi
\u54c1\u8a5e\u7d30\u5206\u985e2 result of Sudachi
\u54c1\u8a5e\u7d30\u5206\u985e3 result of Sudachi
\u54c1\u8a5e\u7d30\u5206\u985e4 result of Sudachi
\u54c1\u8a5e\u7d30\u5206\u985e5 result of Sudachi
\u539f\u5f62 result of Sudachi
```

A data frame with 19565 rows and 12 variable:

A data frame with 19526 rows and 12 variable:

Examples

```
data(review_sudachi_a)
review_sudachi_a |>
  unescape_utf()
```

stop_words	<i>Stop words for morphological analysis</i>
------------	--

Description

Stop words for morphological analysis

Usage

stop_words

Format

A data frame with 310 rows and 1 variable:

stop_word Stop words can be used with `delete_stop_words()`. Escaped by `stringi::stri_escape_unicode()`.

Downloaded from <http://svn.sourceforge.jp/svnroot/slothlib/CSharp/Version1/SlothLib/NLP/Filter/StopWord/word/Jap>

Examples

```
data(stop_words)
stop_words |>
  unescape_utf()
```

synonym	<i>An example of synonym word pairs</i>
---------	---

Description

An example of synonym word pairs

Usage

synonym

Format

A data frame with 25 rows and 2 variables:

from Words to be replaced from. Escaped by `stringi::stri_escape_unicode()`.

to Words to be replaced to.

Examples

```
data(synonym)
synonym |>
  unescape_utf()
```

unescape_utf	<i>Wrapper functions for escape and unescape unicode</i>
--------------	--

Description

Wrapper functions for escape and unescape unicode

Usage

```
unescape_utf(x)
```

```
escape_utf(x)
```

Arguments

x	A dataframe or character vector
---	---------------------------------

Value

A dataframe or character vector

Examples

```
data(review_mecab)
review_mecab |>
  print() |>
  unescape_utf() |>
  print() |>
  escape_utf()
```

Index

* datasets

- neko, 14
- neko_chamame, 15
- neko_ginza, 16
- neko_mecab, 17
- neko_sudachi_a, 18
- review, 22
- review_chamame, 22
- review_ginza, 23
- review_mecab, 24
- review_sudachi_a, 25
- stop_words, 26
- synonym, 26

add_depend_ginza (clean_up), 5

add_group, 2

add_id, 3

add_sentence_no, 4

add_text_id, 4

bigram (draw_bigram_network), 7

bigram_depend (draw_bigram_network), 7

bigram_network (draw_bigram_network), 7

bigram_network_plot
(draw_bigram_network), 7

chamame_field (out_cols_chamame), 19

check_chamame_table (out_cols_chamame),
19

clean_up, 5

cols_chamame (out_cols_chamame), 19

combi_words (combine_words), 6

combine_words, 6

delete_stop_words (clean_up), 5

draw_bigram_network, 7

escape_japanese, 9

escape_utf (unescape_utf), 27

extract_chamame_cols
(out_cols_chamame), 19

html_radio_set (out_cols_chamame), 19

iconv_x, 9

is_radio (out_cols_chamame), 19

make_cmd (moranajp_all), 12

make_cmd_mecab (moranajp_all), 12

make_groups, 10

make_groups_sub (make_groups), 10

make_input (moranajp_all), 12

max_sum_str_length (make_groups), 10

mecab (moranajp_all), 12

mecab_all (moranajp_all), 12

moranajp (moranajp_all), 12

moranajp_all, 12

msg_not_available (out_cols_chamame), 19

neko, 14

neko_chamame, 15

neko_ginza, 16

neko_mecab, 17

neko_sudachi_a, 18

neko_sudachi_b (neko_sudachi_a), 18

neko_sudachi_c (neko_sudachi_a), 18

out_cols (moranajp_all), 12

out_cols_chamame, 19

out_cols_en (moranajp_all), 12

out_cols_ginza (moranajp_all), 12

out_cols_jp (moranajp_all), 12

out_cols_mecab (moranajp_all), 12

out_cols_sudachi (moranajp_all), 12

pos_filter (clean_up), 5

read_html_safely (out_cols_chamame), 19

remove_brk, 21

remove_linebreaks (moranajp_all), 12

replace_words (clean_up), 5

review, 22

review_chamame, 22

`review_ginza`, [23](#)
`review_mecab`, [24](#)
`review_sudachi_a`, [25](#)
`review_sudachi_b` (`review_sudachi_a`), [25](#)
`review_sudachi_c` (`review_sudachi_a`), [25](#)

`select_chamame_fields`
 (`out_cols_chamame`), [19](#)
`separate_cols_ginza` (`morana_jp_all`), [12](#)
`stop_words`, [26](#)
`submit_chamame` (`out_cols_chamame`), [19](#)
`synonym`, [26](#)

`term_lemma` (`clean_up`), [5](#)
`term_pos_0` (`clean_up`), [5](#)
`term_pos_1` (`clean_up`), [5](#)
`trigram` (`draw_bigram_network`), [7](#)

`unescape_utf`, [27](#)

`web_chamame` (`out_cols_chamame`), [19](#)
`web_chamame()`, [13](#)
`word_freq` (`draw_bigram_network`), [7](#)