

Package ‘ncdfgeom’

May 9, 2026

Type Package

Title 'NetCDF' Geometry and Time Series

Version 1.2.2

Description Tools to create time series and geometry 'NetCDF' files.

URL <https://code.usgs.gov/water/ncdfgeom>

BugReports <https://github.com/DOI-USGS/ncdfgeom/issues>

Imports RNetCDF, ncmeta, sf, dplyr, methods, stars, areal

Depends R (>= 3.5)

Suggests testthat, knitr, rmarkdown, pkgdown, jsonlite, zip, ncdf4,
nhdplusTools

License CC0

Encoding UTF-8

Language en-US

VignetteBuilder knitr

RoxygenNote 7.3.3

NeedsCompilation no

Author David Blodgett [aut, cre],
Luke Winslow [ctb]

Maintainer David Blodgett <dblodgett@usgs.gov>

Repository CRAN

Date/Publication 2026-04-22 05:50:02 UTC

Contents

calculate_area_intersection_weights	2
create_cell_geometry	4
read_attribute_data	5
read_geometry	6
read_timeseries_dsg	7

write_attribute_data	8
write_geometry	9
write_timeseries_dsg	10

Index	12
--------------	-----------

calculate_area_intersection_weights
Area Weighted Intersection

Description

Returns the fractional percent of each feature in x that is covered by each intersecting feature in y. These can be used as the weights in an area-weighted mean overlay analysis where x is the data ****source**** and area-weighted means are being generated for the ****target****, y.

This function is a light weight wrapper around the functions [aw_intersect](#) [aw_total](#) and [aw_weight](#) from the [areal](#) package.

Usage

```
calculate_area_intersection_weights(x, y, normalize, allow_lonlat = FALSE)
```

Arguments

x	sf data.frame source features including one geometry column and one identifier column
y	sf data.frame target features including one geometry column and one identifier column
normalize	logical return normalized weights or not. <p>Normalized weights express the fraction of **target** polygons covered by a portion of each **source** polygon. They are normalized in that the area of each **source** polygon has already been factored into the weight. Normalized weights are intended to be used with <code>_intensive_</code> variables.</p> <p>Un-normalized weights express the fraction of **source** polygons covered by a portion of each **target** polygon. This is a more general form that requires knowledge of the area of each **source** polygon to derive area-weighted statistics from **source** to **target**. Un-normalized weights are intended to be used with either <code>_intensive_</code> or <code>_extensive_</code> variables.</p> <p>See details and examples for more regarding this distinction.</p>
allow_lonlat	boolean If FALSE (the default) lon/lat target features are not allowed. Intersections in lon/lat are generally not valid and problematic at the international date line.

Details

Two versions of weights are available:

‘normalize = FALSE’, if a polygon from x (source) is entirely within a polygon in y (target), w will be 1. If a polygon from x (source) is 50 and 50 in each. Weights will sum to 1 per **SOURCE** polygon if the target polygons fully cover that feature.

For ‘normalize = FALSE’ the area weighted mean calculation must include the area of each x (source) polygon as in:

> *in this case, ‘area’ is the area of source polygons and you would do this operation grouped by target polygon id.*

```
> 'sum( (val * w * area), na.rm = TRUE ) / sum(w * area)'
```

If ‘normalize = TRUE’, weights are divided by the target polygon area such that weights sum to 1 per TARGET polygon if the target polygon is fully covered by source polygons.

For ‘normalize = FALSE’ the area weighted mean calculation no area is required as in:

```
> 'sum( (val * w), na.rm = TRUE ) / sum(w)'
```

See examples for illustration of these two modes.

Value

data.frame containing fraction of each feature in x that is covered by each feature in y.

Examples

```
library(sf)

source <- st_sf(source_id = c(1, 2),
                val = c(10, 20),
                geom = st_as_sfc(c(
  "POLYGON ((0.2 1.2, 1.8 1.2, 1.8 2.8, 0.2 2.8, 0.2 1.2))",
  "POLYGON ((-1.96 1.04, -0.04 1.04, -0.04 2.96, -1.96 2.96, -1.96 1.04))")))

source$area <- as.numeric(st_area(source))

target <- st_sf(target_id = "a",
                geom = st_as_sfc("POLYGON ((-1.2 1, 0.8 1, 0.8 3, -1.2 3, -1.2 1))"))

plot(source['val'], reset = FALSE)
plot(st_geometry(target), add = TRUE)

(w <-
  calculate_area_intersection_weights(source[c("source_id", "geom")],
                                    target[c("target_id", "geom")],
                                    normalize = FALSE, allow_lonlat = TRUE))

(res <-
  merge(st_drop_geometry(source), w, by = "source_id"))

(intensive <- sum(res$val * res$w * res$area) / sum(res$w * res$area))
(extensive <- sum(res$val * res$w))
```

```
(w <-
calculate_area_intersection_weights(source[c("source_id", "geom")],
                                   target[c("target_id", "geom")],
                                   normalize = TRUE, allow_lonlat = TRUE))

(res <-
merge(st_drop_geometry(source), w, by = "source_id"))

(intensive <- sum(res$val * res$w) / sum(res$w))
```

create_cell_geometry *Create Cell Geometry*

Description

Creates cell geometry from vectors of X and Y positions.

Usage

```
create_cell_geometry(
  X_coords,
  Y_coords,
  prj,
  geom = NULL,
  buffer_dist = 0,
  regularize = FALSE,
  eps = 1e-10
)
```

Arguments

X_coords	numeric center positions of X axis indices
Y_coords	numeric center positions of Y axis indices
prj	character proj4 string for x and y
geom	sf data.frame with geometry that cell geometry should cover
buffer_dist	numeric a distance to buffer the cell geometry in units of geom projection
regularize	boolean if TRUE, grid spacing will be adjusted to be exactly equal. Only applies to 1-d coordinates.
eps	numeric sets tolerance for grid regularity.

Details

Intersection is performed with cell centers then geometry is constructed. A buffer may be required to fully cover geometry with cells.

Examples

```
dir <- tempdir()
ncf <- file.path(dir, "metdata.nc")

try(zip::unzip(system.file("extdata/metdata.zip", package = "ncdfgeom"), exdir = dir))

if(file.exists(ncf)) {

  nc <- RNetCDF::open.nc(ncf)
  ncmeta::nc_vars(nc)
  variable_name <- "precipitation_amount"
  cv <- ncmeta::nc_coord_var(nc, variable_name)

  x <- RNetCDF::var.get.nc(nc, cv$X, unpack = TRUE)
  y <- RNetCDF::var.get.nc(nc, cv$Y, unpack = TRUE)

  prj <- ncmeta::nc_gm_to_prj(ncmeta::nc_grid_mapping_atts(nc))

  geom <- sf::read_sf(system.file("shape/nc.shp", package = "sf"))
  geom <- sf::st_transform(geom, 5070)

  cell_geometry <- create_cell_geometry(x, y, prj, geom, 0)

  plot(sf::st_geometry(cell_geometry), lwd = 0.25)
  plot(sf::st_transform(sf::st_geometry(geom), prj), add = TRUE)

}
```

read_attribute_data *Read attribute dataframe from NetCDF-DSG file*

Description

Gets attribute data from a NetCDF-DSG file and returns it in a `data.frame`. This function is intended as a convenience to be used within workflows where the netCDF file is already open and well understood.

Usage

```
read_attribute_data(nc, instance_dim)
```

Arguments

`nc` A NetCDF path or url to be opened.
`instance_dim` The NetCDF instance/station dimension.


```
huc_poly <- read_geometry(huc_eta_nc)
plot(sf::st_geometry(huc_poly))
names(huc_poly)
```

read_timeseries_dsg *Read NetCDF-CF timeSeries featuretype*

Description

This function reads a timeseries discrete sampling geometry NetCDF file and returns a list containing the file's contents.

Usage

```
read_timeseries_dsg(nc_file, read_data = TRUE)
```

Arguments

nc_file	character file path to the nc file to be read.
read_data	logical whether to read metadata only or not.

Details

The current implementation checks several NetCDF-CF specific conventions prior to attempting to read the file. The Conventions and featureType global attributes are checked but not strictly required.

Variables with standard_name and/or cf_role of station_id and/or timeseries_id are searched for to indicate which variable is the 'timeseries identifier'. The function stops if one is not found.

All variables are introspected for a coordinates attribute. This attribute is used to determine which variables are coordinate variables. If none are found an attempt to infer data variables by time and timeseries_id dimensions is made.

The coordinates variables are introspected and their standard_names used to determine which coordinate they are. Lat, lon, and time are required, height is not.

Variables with a coordinates attribute are assumed to be the 'data variables'.

Data variables are traversed and their metadata and data content put into lists within the main response list.

See the timeseries vignette for more information.

Value

list containing the contents of the NetCDF file.

References

<https://docs.unidata.ucar.edu/netcdf-java/4.6/userguide/reference/FeatureDatasets/CFpointImplement.html>

write_attribute_data *Write attribute data to NetCDF-CF*

Description

Creates a NetCDF file with an instance dimension, and any attributes from a data frame. Use to create the start of a NetCDF-DSG file. One character length dimension is created long enough to contain the longest provided character string. This function does not implement any CF convention attributes or standard names. Any columns of class date will be converted to character.

Usage

```
write_attribute_data(
  nc_file,
  att_data,
  instance_dim_name = "instance",
  units = rep("unknown", ncol(att_data)),
  overwrite = FALSE
)
```

Arguments

nc_file	character file path to the nc file to be created. If adding to a file, it must already have the named instance dimension.
att_data	data.frame with instances as columns and attributes as rows.
instance_dim_name	character name for the instance dimension. Defaults to "instance"
units	character vector with units for each column of att_data. Defaults to "unknown" for all.
overwrite	boolean overwrite existing file? Will append if FALSE.

Examples

```
sample_data <- sf::st_set_geometry(sf::read_sf(system.file("shape/nc.shp",
                                                         package = "sf")),
                                  NULL)
example_file <- write_attribute_data(tempfile(), sample_data,
                                    units = rep("unknown", ncol(sample_data)))

try({
  ncdump <- system(paste("ncdump -h", example_file), intern = TRUE)
  cat(ncdump, sep = "\n")
}, silent = TRUE)
```

write_geometry	<i>Write geometries and attributes to NetCDF-CF</i>
----------------	---

Description

Creates a file with point, line or polygon instance data ready for the extended NetCDF-CF time-Series featuretype format.

Will also add attributes if provided data has them.

Usage

```
write_geometry(
  nc_file,
  geom_data,
  instance_dim_name = NULL,
  variables = list()
)
```

Arguments

nc_file	character file path to the nc file to be created.
geom_data	sf data.frame with POINT, LINestring, MULTILINESTRING, POLYGON, or MULTIPOLYGON geometries. Note that three dimensional geometries are not supported.
instance_dim_name	character Not required if adding geometry to a NetCDF-CF Discrete Sampling Geometries timeSeries file. For a new file, will use package default – "instance" – if not supplied.
variables	character If a an existing netCDF files is provided, this list of variables that should be related to the geometries.

References

1. <https://cfconventions.org/cf-conventions/cf-conventions.html>

Examples

```
hucPolygons <- sf::read_sf(system.file('extdata', 'example_huc_eta.json', package = 'ncdfgeom'))

hucPolygons_nc <- ncdfgeom::write_geometry(nc_file=tempfile(),
                                           geom_data = hucPolygons)

try({
  ncdump <- system(paste("ncdump -h", hucPolygons_nc), intern = TRUE)
  cat(ncdump ,sep = "\n")
}, silent = TRUE)
```

write_timeseries_dsg *Write time series to NetCDF-CF*

Description

This function creates a timeseries discrete sampling geometry NetCDF file. It uses the orthogonal array encoding to write one data.frame per function call. This encoding is best suited to data with the same number of timesteps per instance (e.g. geometry or station).

Usage

```
write_timeseries_dsg(
  nc_file,
  instance_names,
  lats,
  lons,
  times,
  data,
  alts = NA,
  data_unit = "",
  data_prec = "double",
  data_metadata = list(name = "data", long_name = "unnamed data"),
  time_units = "days since 1970-01-01 00:00:00",
  instance_dim_name = "instance",
  dsg_timeseries_id = "instance_name",
  coordvar_long_names = list(instance = "Station Names", time = "time of measurement",
    lat = "latitude of the measurement", lon = "longitude of the measurement", alt =
    "altitude of the measurement"),
  attributes = list(),
  add_to_existing = FALSE,
  overwrite = FALSE
)
```

Arguments

nc_file	character file path to the nc file to be created.
instance_names	character or numeric vector of names for each instance (e.g. station or geometry) to be added to the file.
lats	numeric vector of latitudes
lons	numeric vector of longitudes
times	POSIXct vector of times. Must be of type POSIXct or an attempt to convert it will be made using as.POSIXct(times).
data	data.frame with each column corresponding to an instance. Rows correspond to time steps. nrow must be the same length as times. Column names must match instance names.

alts	numeric vector of altitudes (m above sea level) (Optional)
data_unit	character vector of data units. Length must be the same as number of columns in data parameter.
data_prec	character precision of observation data in NetCDF file. Valid options: 'short' 'integer' 'float' 'double' 'char'.
data_metadata	list A named list of strings: list(name='ShortVarName', long_name='A Long Name')
time_units	character units string in udunits format to use for time. Defaults to 'days since 1970-01-01 00:00:00'
instance_dim_name	the character name to use for the instance used in 'instance_names'
dsg_timeseries_id	the character name to use for the instance used in the timeseries id
coordvar_long_names	list values for long names on coordinate variables. Names should be 'instance', 'time', 'lat', 'lon', and 'alt.'
attributes	list An optional list of attributes that will be added at the global level. See details for useful attributes.
add_to_existing	boolean If TRUE and the file already exists, variables will be added to the existing file. See details for more.
overwrite	boolean unless set to true, error if file exists.

Details

Suggested Global Variables: c(title = "title", abstract = "history", provider site = "institution", provider name = "source", description = "description")

Note regarding add_to_existing: add_to_existing = TRUE should only be used to add variables to an existing NetCDF discrete sampling geometry file. All other inputs should be the same as are already in the file. If the functions is called with add_to_existing=FALSE (the default), it will overwrite an existing file with the same name. The expected usage is to call this function repeatedly only changing the data, data_unit, data_prec and data_metadata inputs.

See the timeseries vignette for more information.

References

1. <https://docs.unidata.ucar.edu/netcdf-java/4.6/userguide/reference/FeatureDatasets/CFpointImplement.html>
2. https://cfconventions.org/cf-conventions/cf-conventions.html#_orthogonal_multidimensional_array_representation
3. <https://cfconventions.org/Data/cf-conventions/cf-conventions-1.7/build/cf-conventions.html#time-series-data>

Index

`aw_intersect`, [2](#)

`aw_total`, [2](#)

`aw_weight`, [2](#)

`calculate_area_intersection_weights`, [2](#)

`create_cell_geometry`, [4](#)

`read_attribute_data`, [5](#)

`read_geometry`, [6](#)

`read_timeseries_dsg`, [7](#)

`write_attribute_data`, [8](#)

`write_geometry`, [9](#)

`write_timeseries_dsg`, [10](#)